

	RUT230	RUT240	RUT950	RUT955
TECHNOLOGY				
4G (LTE)	-	CAT 4 up to 70 Mbps	CAT 4 up to 100 Mbps	CAT 4 up to 100 Mbps
3G	Up to 14.4 Mbps	Up to 42 Mbps	Up to 42 Mbps	Up to 42 Mbps
2G	Up to 236.8 kbps	Up to 236.8 kbps	Up to 236.8 kbps	Up to 236.8 kbps
GNSS	-	-	-	✓
WiFi	Up to 150 Mbps	Up to 150 Mbps	Up to 300 Mbps	Up to 300 Mbps
GPRS	✓	✓	✓	✓
Ethernet	2 ports	2 ports	4 ports	4 ports
SMS	✓	✓	✓	✓
Hardware				
RS232	-	-	-	✓
RS485	-	-	-	✓
Digital output	1	1	-	2
DIN – digital input	1	1	-	2
AIN - analog input	-	-	-	1
Micro SD	-	-	-	✓
1x SIM Card	✓	✓	✓	✓
2x SIM Card (Dual-SIM)	-	-	✓	✓
3x LAN 10/100Mbps Ethernet ports	-	-	✓	✓
1x LAN 10/100Mbps Ethernet port	✓	✓	-	-
1x WAN 10/100Mbps Ethernet ports	✓	✓	✓	✓
IEEE 802.11b/g/n WiFi standards	✓	✓	✓	✓
Durable aluminum housing	✓	✓	✓	✓

	RUT230	RUT240	RUT950	RUT955
USB A socket for external devices	-	-	-	✓
2 pin industrial DC power socket	-	-	✓	✓
Power over Ethernet (not compliant with IEEE 802.3af - 2003)	-	-	✓	✓
I/O connector	-	-	-	✓
Mobile antenna type	1 x SMA for 3G	2x SMA for LTE	2 x SMA	2 x SMA
WiFi antenna type	1 x RP-SMA	1 x RP-SMA	2 x RP-SMA	2 x RP-SMA
GNSS antenna type	-	-	-	1 x SMA
Input voltage range	9 - 30 VDC	9-30 VDC	9-30 VDC	9-30 VDC
Operating temperature range	-40 °C to 75 °C	-40°C to 75° C	-45°C to 80° C	-40°C to 75° C
Storage temperature range	-45 °C to 80 °C	-45°C to 80° C	-45° to 80° C	-45°C to 80° C
Power consumption	< 5W	< 5W	< 7W	< 7W
Mounting options	DIN Rail, Wall	DIN RailWall	DIN Rail, Wall	DIN Rail, Wall
LED indication	2x connection status, 5x connection strength, 1x Power	3x connection status, 5x connection strength, 1x Power	1x bi-color connection status, 5x connection strength, 4x LAN status, 1x Power	1x bi-color connection status, 5x connection strength, 4x LAN status, 1x Power
Firmware				
Remote configuration over SMS	-	-	✓	✓
Bridge mode	-	✓	✓	✓
Automatic and manual operator selection	-	-	✓	✓
Static routes	✓	✓	✓	✓
PPPoE	-	-	✓	✓
NTP	✓	✓	✓	✓
Wireless Hotspot	✓	✓	✓	✓
Wireless Client	✓	✓	✓	✓

	RUT230	RUT240	RUT950	RUT955
Wireless AP	✓	✓	✓	✓
Ping reboot	✓	✓	✓	✓
Periodic reboot	✓	✓	✓	✓
Real-time graphs	✓	✓	✓	✓
Backup WAN	✓	✓	✓	✓
Mobile Traffic counter	✓	✓	✓	✓
Connection status overview bar	✓	✓	✓	✓
Configuration backup/restore	✓	✓	✓	✓
VRRP	✓	✓	✓	✓
IPsec	✓	✓	✓	✓
GRE Tunnel	✓	✓	✓	✓
OpenVPN	✓	✓	✓	✓
PPTP	✓	✓	✓	✓
SNMP	✓	✓	✓	✓
SNMP Trap	✓	✓	✓	✓
Send/receive SMS	✓	✓	✓	✓
Status via SMS	✓	✓	✓	✓
SMS reboot	✓	✓	✓	✓
Mobile enable/disable via SMS	✓	✓	✓	✓
Wireless enable/disable via SMS	✓	✓	✓	✓
OpenVPN enable/disable via SMS	✓	✓	✓	✓
Web Filter	✓	✓	✓	✓
Mobile on Demand	✓	✓	✓	✓
Mobile Data Limit	✓	✓	✓	✓
Configuration Profiles	✓	✓	✓	✓

	RUT230	RUT240	RUT950	RUT955
Event logging	✓	✓	✓	✓
QoS	✓	✓	✓	✓
Restore Point	-	-	✓	✓
Call Utilities	✓	✓	✓	✓
SIM switch	-	-	✓	✓
FOTA (Firmware Over The Air)	✓	✓	✓	✓
Event reporting (via Email/SMS)	-	-	✓	✓
Network Scanner with Topology display	-	-	✓	✓
Disable Roaming	✓	✓	✓	✓
SMS gateway	✓	✓	✓	✓
OSPF	-	-	✓	✓
Access control safety	✓	✓	✓	✓
SIM Idle protection	-	-	✓	✓
VLAN	✓	✓	✓	✓
CLI	✓	✓	✓	✓
Firewall	✓	✓	✓	✓
IP/MAC filter	✓	✓	✓	✓
TR-069	-	-	✓	✓
DHCP server	✓	✓	✓	✓
Dynamic DNS	✓	✓	✓	✓
RMS support	✓	✓	✓	✓